

PENNZOIL 4T MOTOR OIL

PRODUCT DESCRIPTIONS

PENNZOIL 4T MOTOR OIL is motor oil designed for small air-cooled 4-cycle engines. It contains a balanced blend of select high performance, high quality base stocks, and a special proprietary additive package. PENNZOIL 4T MOTOR OIL is engineered to provide unsurpassed wears protection, engine cleanliness, and oxidation resistance, as well, as consistent viscosity.

APPLICATION

PENNZOIL 4T MOTOR OIL is used in small air-cooled engines that 4-Stock motorcycle,

power mowers, tillers, tractors, compressor generators, and the like. **PENNZOIL 4T MOTOR OIL** is detergent motor oil. **PENNZOIL 4T MOTOR OIL** exceeds the requirements of API Service Classification SF or any combination such as SF/CD.

BENEFITS

- Reduces engine wear and extends engine life
- Protects engine under severe operating conditions
- Retards harmful deposit formations on vital engine parts
- Exceeds API Service SF/CD

TYPICAL PHYSICAL AND CHEMICAL PROPERTIES PENNZOIL 4T MOTOR OIL

TEST	METHOD	TYPICAL RESULTS
SAE Viscosity Grade	SAE J300	40
API Service	SAE J183	SF/CD
Pour Point, max °C	ASTM D-97	-9
Flash Point, min °C	ASTM D-92	273
Viscosity		
@ 40 °C, cSt	ASTM D-445	157
@ 100 °C, cSt	ASTM D-445	15.2
Viscosity Index, min	ASTM D-2270	97
Copper Strip Corrosion	ASTM D-130	2a
Total Base Number, min mg KOH/g	ASTM D-2896	6.5