

PENNZOIL SEMI SYNTHETIC MOTOR OIL

High quality semi-synthetic gasoline engine oil

Description Product

Pennzoil Semi Synthetic Motor Oil is a semi synthetic engine oil formulated from high quality synthetic base oil and highly refined paraffinic base stocks with specially selected additives. It provides outstanding thermal stability and extensive service life. It maintains thick oil films for maximum protection in hard working engines.

Pennzoil Semi Synthetic Motor Oil resists viscosity breakdown under the high temperature and high shear conditions which are the benefits from its high quality additives including specially selected Viscosity Index Improver additive. It keeps the engine clean and gives superb wear protection.

Application

Pennzoil Semi Synthetic Motor Oil is designed

for all gasoline engines where a SAE 10W-40 motor oil is recommended. It exceeds the performance requirements of API Service SM.

Benefit

- Excellent engine protection
- Helps engine running smoothly and extends the engine life
- Provides better protection with the high film strength and special additives
- Keeps engine clean and reduces the deposit from combustion
- Stays in viscosity grade
- Suitable for most high performance passenger cars, SUV and APV with gasoline engines
- Exceeds API SM Service Classification

TYPICAL PHYSICAL AND CHEMICAL PROPERTIES PENNZOIL SEMI SYNTHETIC MOTOR OIL

TEST	METHOD	TYPICAL RESULTS
SAE Viscosity Grade	SAE J300	10W-40
API Service	SAE J183	SM
Pour Point, °C	ASTM D-97	-30
Flash Point, °C	ASTM D-92	236
Viscosity		
@ 40 °C, cSt	ASTM D-445	98.46
@ 100 °C, cSt	ASTM D-445	14.88
Viscosity Index	ASTM D-2270	158
Low Temperature Viscosity, Vis (cP) at temperature (°C) Max	ASTM D-5293	5,900 @-25C
Total Base Number, mg KOH/g	ASTM D-2896	7.5